

CLAIMS

What is claimed is:

1. A method of performing a discrete cosine transform (DCT) using a microprocessor
5 having an instruction set that includes SIMD floating point instructions, wherein the
method comprises:

receiving a block of integer data having C columns and R rows, wherein the block
of integer data is indicative of a portion of an image; and

for each row,

- 10 loading the row data into registers;
converting the row data into floating point form, wherein the registers each
hold two floating point row data values; and
performing a plurality of weighted-rotation operations on the values in the
registers, wherein the weighted-rotation operations are performed
15 using SIMD floating point instructions.

2. The method of claim 1, wherein said converting is accomplished using the pi2fw
instruction.

3. The method of claim 1, wherein said weighted-rotation operations are accomplished
using the pswap, pfmul, and pfpnacc instructions.

- 20 4. The method of claim 1, further comprising:

for each row,

altering the arrangement of values in the registers;

performing a second plurality of weighted-rotation operations on the
values in the registers;

again altering the arrangement of the values in the registers;

5 performing a third plurality of weighted-rotation operations on the values
in the registers;

yet again altering the arrangement of the values in the registers; and

performing a fourth plurality of weighted-rotation operations on the values
in the registers to obtain intermediate floating point values.

10 5. The method of claim 4, further comprising:

for each row,

storing the intermediate floating point values to an intermediate buffer.

6. The method of claim 5, further comprising:

for two columns at a time,

15 loading data from two columns of intermediate data into each of a
plurality of registers;

performing a plurality of weighted-rotation operations on the values in the
registers, wherein the weighted-rotation operations for two
columns are performed in parallel using SIMD floating point
20 instructions.

7. The method of claim 6, wherein said weighted-rotation operations for two columns at a time are accomplished using pfmul, pfsb, and pfadd instructions.

8. The method of claim 6, further comprising:

for two columns at a time,

5 as each weighted-rotation operation is done, storing weighted-rotation operation results to the intermediate buffer.

9. The method of claim 8, further comprising:

for two columns at a time,

10 retrieving weighted-rotation operation results from the intermediate buffer;
performing a second plurality of weighted-rotation operations on the retrieved values;

again storing weighted-rotation operation results to the intermediate buffer as the weighted-rotation operations of the second plurality are done;

15 again retrieving weighted-rotation operation results from the intermediate buffer;

performing a third plurality of weighted-rotation operations on the retrieved values;

20 yet again storing weighted-rotation operation results to the intermediate buffer as the weighted-rotation operations of the third plurality are done;

yet again retrieving weighted-rotation operation results from the
intermediate buffer;

performing a fourth plurality of weighted-rotation operations on the
retrieved values;

5 converting the weighted-rotation operation results from the fourth plurality
to integer results.

10. The method of claim 9, further comprising:

for two columns at a time, writing the integer results to an output buffer.

11. A method of performing a discrete cosine transform (DCT) using a microprocessor
10 having an instruction set that includes SIMD floating point instructions, wherein the
method comprises:

receiving a block of integer data having C columns and R rows; and

for two columns at a time,

loading column data into registers;

15 converting the column data into floating point form, wherein the registers
each hold a floating point column data value from two columns;
and

performing a plurality of weighted-rotation operations on the values in the
registers, wherein the weighted-rotation operations for two
20 columns are performed in parallel using SIMD floating point
instructions.

12. The method of claim 11, wherein said weighted-rotation operations are accomplished using pfmul, pfsb, and pfadd instructions.

13. The method of claim 11, further comprising:

for two columns at a time,

5 as each weighted-rotation operation is done, storing weighted-rotation operation results to an intermediate buffer.

14. The method of claim 13, further comprising:

for two columns at a time,

10 retrieving weighted-rotation operation results from the intermediate buffer; performing a second plurality of weighted-rotation operations on the retrieved values;

again storing weighted-rotation operation results to the intermediate buffer as the weighted-rotation operations of the second plurality are done;

15 again retrieving weighted-rotation operation results from the intermediate buffer;

performing a third plurality of weighted-rotation operations on the retrieved values;

20 yet again storing weighted-rotation operation results to the intermediate buffer as the weighted-rotation operations of the third plurality are done;

yet again retrieving weighted-rotation operation results from the
intermediate buffer;

performing a fourth plurality of weighted-rotation operations on the
retrieved values;

5 converting the weighted-rotation operation results from the fourth plurality
to integer results.

15. The method of claim 14, further comprising:

for two columns at a time, writing the integer results to an output buffer.

10 16. A computer system comprising:

a processor having an instruction set that includes SIMD floating point
instructions; and

a memory coupled to the processor, wherein the memory stores software
instructions executable by the processor to implement the method of
receiving a block of integer data having C columns and R rows, wherein
15 the block of integer data is indicative of a portion of an image; and

for each row,

loading the row data into registers;

converting the row data into floating point form, wherein the registers each

20 hold two floating point row data values; and

performing a plurality of weighted-rotation operations on the values in the registers, wherein the weighted-rotation operations are performed using SIMD floating point instructions.

- 5 17. A carrier medium comprising software instructions executable by a microprocessor having an instruction set that includes SIMD floating point instructions to implement a method of performing discrete cosine transform (DCT), wherein the method comprises:
- receiving a block of integer data having C columns and R rows, wherein the block of integer data is indicative of a portion of an image; and
- 10 for each row,
- loading the row data into registers;
- converting the row data into floating point form, wherein the registers each hold two floating point row data values; and
- performing a plurality of weighted-rotation operations on the values in the registers, wherein the weighted-rotation operations are performed
- 15 using SIMD floating point instructions.